

Fisa tehnica centrale termice pentru busteni de lemn UNILINE TITAN

Model	TITAN T-4 68	TITAN T-5 78	TITAN T-6 98
Putere termica maxima (kW)	68	79	98
Dimensiuni usa de alimentare (mm)	490x450	490x450	650x500
Putere termica nominala (kW)	68	78	95
Randament (%)	84	86	85
Racord de umplere/golire (toli)	Ø 1/2"	Ø 1/2"	Ø 1/2"
Racorduri tur/retur (toli)	Ø 2"	Ø 2"	Ø 2"
Diametru racord cos de fum (mm)	Ø 200	Ø 200	Ø 250
Inaltime (mm)	1270	1335	1435
Latime - cu izolatie termica (mm)	700	705	850
Latime (mm)	655	660	805
Adancime (fata - spate) (mm)	1070	1310	1500
Greutate (kg)	500	580	820
Continut de apa (litri)	350	420	520
Presiune de lucru (bar)	2	2	2
Gama de temperaturi de lucru (°C)	50 ÷ 90	50 ÷ 90	50 ÷ 90
Presiune de proba (bar)	4	4	4
Tiraj necesar la cos (mbar)	0.2	0.2	0.2
Dimensiuni focar (mm)	850x490x590	1050x490x620	1250x650x620
Clasa centralei conform EN 303-5:2012	Clasa 4	Clasa 4	Clasa 4